FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION				FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME GULF 2000, "INC.		AND A CONTRACTOR OF THE		POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bidg, Number) OR P.O. ROUTE AND BOX NUMBER 2000 GULF BOULEVARD OTHER DESCRIPTION (Lot and Block Numbers, etc.)				COMPANY NAIC NUMBER
LOT 9, BLK.11, RE-RI	EVISED MA	P OF INDIAN BE	ACH (PLUS) PB.5 PG.6
INDIAN ROCKS BEACH			STATE	ZIP CODE
•	OOD INSUIDA	PINELLAS COUN	PLORIDA	
rovide the following from the proper FIRM (See	Instructions):	NCE RATE MAP (FIRM)	INFORMATION	
1. COMMUNITY NUMBER			·	
125117 0003	3. SUFFIX B	4 PATE OF FIRM INDEX 3/2/83	5. FIRM ZONE A-11	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
Indicate the elevation datum system used on the state of the community's BFE: feet N				Other (describe on back) or this building site, indicate
SECTI	ON C BUILDI	NG ELEVATION INFORM	MATION	· · · · · · · · · · · · · · · · · · ·
of 10 feet NGVD (or other FIF (b). FIRM Zones V1-V30, VE, and V (with BFE the selected diagram, is at an elevation of (c). FIRM Zone A (without BFE). The floor use below (check one) the highest grade a (d). FIRM Zone AO. The floor used as the refe one) the highest grade adjacent to the built level) elevated in accordance with the com 3. Indicate the elevation datum system used in under Comments on Page 2). (NOTE: If the the FIRM [see Section B, Item 7], then convequation under Comments on Page 2.)	d as the reference level from ding. If no flood imunity's flood determining the elevation datule of th	of the lowest horizontal at feet NGVD (or other FIF noe level from the selected building. In the selected diagram is depth number is available in management ordinary above reference level of mused in measuring the ons to the datum system of the selected for the datum system of the selected for	and datum—see S and diagram is feet a ale, is the building ace? Yes evations: X NG elevations is differenced on the FIRM	ection B, Item 7). feet above or or below (check or below (check or feerence is lowest floor (reference No Unknown VD '29 Other (describe
 Elevation reference mark used appears on F 	IRM: 🗌 Yes [No (See Instructions	on Page 4)	i ,
(NOTE: Use of construction drawings is only case this certificate will only be valid for the build be required once construction is complete.	A actual construence of the second construen	uction construction of construction of construction of construction	drawings ne reference leve . A post-construc	ction Elevation Certificate
6. The elevation of the lowest grade immediate Section B, Item 7).	ly adjacent to th	ne bullding is:	9.LO feet NGVD	(or other FIRM datum-see
All the state of the	SECTION D C	OMMUNITY INFORMAT	ON	
If the community official responsible for verify is not the "lowest floor" as defined in the comfloor" as defined by the ordinance is: Date of the start of construction or substantial.	ing building ele	yations specifies that the lain management ordinal	reference level ince, the elevation	ndicated in Section C, Item 1 of the building's "lowest B, Item 7).

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE), V1–V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

21111	
CERTIFIED NAME PENNY	LICENSE NUMBER (or Affix Seal) #4931
LAND SURVEYOR	COMPANY NAMETR. PENNY & ASSOCIATES, INC.
10730: 102 AVENUE N.	CITY SEMINOLE FLATE 3778 ZIP
SIGNATUREY James K	DATE 1/12/00 PHONE 813-398-4360
Coples should be made of this Certi	ficate for: 1) community official, 2) insurance agent/company, and 3) building owner.
COMMENTS:	A STATE OF THE STA
and the second s	
• • •	
the place of the party	
WHEN THE WAY I	
	The same of the Contract of the same of th
, ON BLAB	WITH ON PILES,
A V ZONES ZONES	PIERS, OR COLUMNS
	ZONES ZONES ZONES
LEVEL	ALEFERENCE LEVEL
ELEVATION REFERENCE	ADJACENT GRADE REFERENCE LEVEL REFERENCE LEVEL
TEVEL	<u> </u>

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor. Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.